




DR1

alkè
ELECTRIC VEHICLES

ATX 340ED



	340 ED	weight [kg]
TYPE-APPROVAL CAB SEATS		
EU on-road type-approval	N1	
seats inside the cab	4	
right-hand drive	Δ	+ 0.0

	340 ED	weight [kg]
PERFORMANCE		
top speed [km/h]	44	
maximum negotiable slope (with high-performance batteries) [%]	25	
maximum autonomy (R101 test with 10.0kWh battery in SPORT mode: 74 km)		
Lead-Acid 10 kWh [km]	—	
Lead-Acid 14.4 kWh [km]	85	
Gel 8.7 kWh [km]	—	
Gel 13.2 kWh [km]	75	
Lithium (LiFePO4) 10 kWh [km]	75	
Lithium (LiFePO4) 20 kWh [km]	145	

	340 ED	weight [kg]
DIMENSIONS		
A length (chassis version) [mm]	3.980	
B length (version with cargo bed) [mm]	4.290 ⁽¹⁾ 4.490 ⁽²⁾	
C vehicle cab width (without rear-view mirrors) [mm]	1.215	
D vehicle cab width (with wing mirrors closed) [mm]	1.380	
E vehicle cab width (with wing mirrors open) [mm]	1.650	
F cab height (with standard tyres) [mm]	1.890	
G vehicle height with beacon light (with standard tyres) [mm]	1.980	
H wheelbase [mm]	2.890 ⁽¹⁾ 2.990 ⁽²⁾	
I approach angle [°]	40	

	340 ED	weight [kg]
J departure angle [°]	9 ⁽¹⁾ 8 ⁽²⁾	
K rear axle distance from ground [mm]	130	
L maximum loading bed length [mm]	1.800 ⁽¹⁾ 2.000 ⁽²⁾	
M maximum loading bed width [mm]	1.500	

	340 ED	weight [kg]
WEIGHTS CAPACITY AND TOWING		
UVW unloaded vehicle weight (chassis version with battery)		
Lead-Acid 10 kWh [kg]	—	
Lead-Acid 14.4 kWh [kg]	1.290	
Gel 8.7 kWh [kg]	—	
Gel 13.2 kWh [kg]	1.290	
Lithium (LiFePO4) 10 kWh [kg]	995	
Lithium (LiFePO4) 20 kWh [kg]	1085	
GVW gross vehicle weight (max weight for fully-loaded vehicle) [kg]	2.150	
GCW gross combined weight (max weight for fully-loaded vehicle + trailer) [kg]	4.100	
maximum towing capacity (on road braked trailer) [kg]	2.000	
maximum traction power [N]	5.230	
maximum towing capacity (not on road braked trailer) [kg]	3.000	
maximum chassis load capacity (= GVW - UVW)		
Lead-Acid 10 kWh [kg]	—	
Lead-Acid 14.4 kWh [kg]	860	
Gel 8.7 kWh [kg]	—	
Gel 13.2 kWh [kg]	860	
Lithium (LiFePO4) 10 kWh [kg]	1.155	
Lithium (LiFePO4) 20 kWh [kg]	1.065	



	340 ED	weight [kg]
MOTOR CONTROLLER		
48V AC asynchronous induction electric motor	.	
maximum motor power [kW]	14	
maximum motor torque [Nm]	113	
CURTIS 48V control electronics	.	
vehicle performance settings (ECO and SPORT)	.	
auxiliary cooling system for motor / controller	Δ	+ 2.0
Vehicle Body Computer (VBC)	Δ	
12M STD Cloud Service license	Δ	
12M PRO Cloud Service license	Δ	
TRANSMISSION		
transmission with electronic speed variation	.	
rear wheel drive	.	
heavy duty differential unit	.	
SUSPENSIONS		
front suspension with MacPherson type independent wheels	.	
rear suspension with De-Dion bridge and stabiliser bar	.	
BRAKES		
front hydraulic discs brakes and rear hydraulic drum brakes	.	
rear hydraulic drum brakes with mechanical servobrake	.	
parking brake	.	
regenerative brake	.	
STEERING		
rack and pinion steering	.	
electric power steering (EPS)	Δ	+ 7.0
minimum turning radius internal [mm]	4,110 ⁽¹⁾ 4,130 ⁽²⁾	
BODY CHASSIS		
white body	.	
customised body colour	Δ	+ 0.0
steel chassis with anti-corrosion treatment and powder coating finish	.	
impact-resistant polyethylene front and rear bumpers	.	
SAFETY		
3-point seat belt for driver and passenger(s)	.	
immobilizer and presence sensor on driver's seat	.	
steering lock with key	.	
horn / reverse buzzer	.	
rear view camera with LCD rear view monitor	Δ	
forward gear buzzer activable from dashboard	Δ	
safety switch inside the cab for 48 V drive battery	.	
safety switch inside the cab for 12 V service battery	.	
tyre repair kit	.	
LIGHTS		
front and rear lights in road style	.	
full LED rear lights	.	
rear fog light and LED reversing light	.	
LED DRL lights	.	
orange flashing LED on cab roof	Δ	+ 2.0
blue flashing LED on cab roof	Δ	+ 2.0
CAB COMFORT		
timed heated windshield	.	
electric demister	Δ	+7

	340 ED	weight [kg]
Webasto heating (as an alternative to electric demister)	Δ	+ 13.0
air-conditioning	Δ	+ 25.0
adjustable seats	.	
front doors	.	
front doors with sliding windows	Δ	+ 0.0
rear doors	.	
armrests	Δ	+ 3.5
headrests	.	
rear seat bench	!	+ 22.0
cab interior lighting	.	
sun visors	Δ	
rear-view camera with internal LCD color monitor	Δ	
car audio system AM/FM/DAB/DAB+ with USB and Bluetooth	Δ	
rear speakers for 4-seats models	Δ	
openable front windscreen	.	
central door locks with remote control	Δ	
windscreen wiper with windscreen washer	.	
DASHBOARD		
ECO / SPORT selector	.	
12V 10A socket	.	
speedometer (km / mph)	.	
hour meter	.	
indicators	battery state of charge	battery capacity
	inverter temperature	current delivered by inverter
	motor temperature	
dashboard LCD colour display	.	
warning lights	indicators	doors lock
	lifted cargo bed	heated windshield
	low beam headlights	side lights
	electric demister	rear fog light
	beacon light	Webasto fuel shortage
	forward gear	battery on electric motor charge status
	emergency lights	overheating
		neutral gear
		aux 1
		aux 2
BATTERY		
type	Lead-Acid 10 kWh	—
	Lead-Acid 14.4 kWh	.
	Gel 8.7 kWh	—
	Gel 13.2 kWh	Δ
	Lithium (LiFePO4) 10 kWh	Δ
	Lithium (LiFePO4) 20 kWh	Δ
number of batteries	Lead-Acid 10 kWh	—
	Lead-Acid 14.4 kWh	24x2V
	Gel 8.7 kWh	—
	Gel 13.2 kWh	24x2V
	Lithium (LiFePO4) 10 kWh	1x48V
	Lithium (LiFePO4) 20 kWh	1x48V

. as standard Δ optional ! compatible but not type-approved for road circulation
— not available ⁽¹⁾ vehicle with standard wheelbase ⁽²⁾ vehicle with long wheelbase



			340 ED	weight [kg]	
estimated battery life	Lead-Acid 10 kWh	[cycles]	—		
	Lead-Acid 14.4 kWh	[cycles]	1.500		
	Gel 8.7 kWh	[cycles]	—		
	Gel 13.2 kWh	[cycles]	1.200		
	Lithium (LiFePO4) 10 kWh	[cycles]	2.000		
	Lithium (LiFePO4) 20 kWh	[cycles]	2.000		
estimated battery charge time	Lead-Acid 10 kWh	[hours]	—		
	Lead-Acid 14.4 kWh	[hours]	8		
	Gel 8.7 kWh	[hours]	—		
	Gel 13.2 kWh	[hours]	11		
	Lithium (LiFePO4) 10 kWh	[hours]	3.5		
	Lithium (LiFePO4) 20 kWh	[hours]	6.5		
	Lithium (LiFePO4) 10 kWh with quick charge	[hours]	1.5		
	Lithium (LiFePO4) 20 kWh with quick charge	[hours]	2.6		
	consumption for complete recharge	Lead-Acid 10 kWh	[kWh]	—	
		Lead-Acid 14.4 kWh	[kWh]	13	
Gel 8.7 kWh		[kWh]	—		
Gel 13.2 kWh		[kWh]	12		
Lithium (LiFePO4) 10 kWh		[kWh]	8.4		
Lithium (LiFePO4) 20 kWh		[kWh]	16.8		
12 V services auxiliary battery			•		
battery charge on vehicle (PFC active)	(power supply 230V 16A 50-60Hz)		•		
external quick battery charge (Lithium only)	(power supply 380V 16A 50-60Hz)	Δ	(ext.) +15.0		
battery swap system	Lead-Acid 14.4 kWh		•		
	Gel 13.2 kWh		•		
battery top-up	Lead-Acid 10 kWh		Δ	+ 0.0	
	Lead-Acid 14.4 kWh		Δ	+ 0.0	

CONFIGURATIONS AND CARGO AREA ACCESSORIES

dropside body with manual tipping (aluminium drop sides H30 cm)	130 x 123 cm	—	+ 105.0
	180 x 123 cm	Δ ⁽¹⁾	+ 130.0
	200 x 140 cm	Δ ⁽²⁾	+ 160.0
flatbed for special configurations	130 x 123 cm	—	+ 80.0
	180 x 123 cm	Δ ⁽¹⁾	+ 90.0
	200 x 140 cm	Δ ⁽²⁾	+ 120.0

		340 ED	weight [kg]
mesh sides extension H55 cm with rear drop side with upwards opening	for body 130 x 123 cm	—	+ 25.0
	for body 180 x 123 cm	Δ ⁽¹⁾	+ 29.0
COMBI mesh sides extension H55 cm 150 x 123 cm with rear drop side	for body 200 x 140 cm	Δ ⁽²⁾	+ 30.0
		Δ ⁽²⁾	+ 30.0
electro-hydraulic tipping for dropside body unit	for body 130 x 123 cm	—	+ 14.0
	for body 150 x 123 cm	Δ ⁽²⁾	
	for body 180 x 123 cm	Δ ⁽¹⁾	+ 15.0
	for body 200 x 140 cm	Δ ⁽²⁾	+ 15.0
dropside body 180 x 123 cm with three side hydraulic tipping		Δ ⁽¹⁾	+ 190.0
		—	+ 25.0
tarpaulin body H108 cm openable on three sides for dropside body	for body 130 x 123 cm	—	+ 25.0
		Δ ⁽¹⁾	+ 30.0
tarpaulin body H108 cm openable on three sides for dropside body	for body 180 x 123 cm	Δ ⁽¹⁾	+ 30.0
		Δ ⁽²⁾	+ 35.0
tarpaulin body H108 cm openable on three sides for dropside body	for body 200 x 140 cm	Δ ⁽²⁾	+ 35.0
		Δ	+ 0.0
custom colour for tarpaulin body		Δ ⁽²⁾	+ 35.0
tarpaulin body H110 cm for COMBI 150 x 123 cm dropside body		!	+ 45.0
removable rear seats kit with two independent seats, platform and 2-points seat belts		Δ ⁽¹⁾	+ 30.0
tarpaulin roof H105 for rear seats kit		! ⁽¹⁾	+ 75.0
ambulance body equipped with spine board and box/seat for medical staff		Δ ⁽¹⁾	+ 20.0
roof for ambulance body		Δ ⁽¹⁾	+ 130.0
box van body H122 cm 180 x 125 cm with sliding doors (2 per side)		Δ ⁽²⁾	+ 170.0
box van body H122 cm 200 x 140 cm with sliding doors (2 per side)		Δ ⁽¹⁾	+ 150.0
box van body with side roller shutters H132 cm 180 x 125 cm		Δ ⁽²⁾	+ 180.0
box van body with side roller shutters H132 cm 200 x 140 cm		Δ ⁽¹⁾	+ 8.0
set 2 shelves for box van body with sliding doors (each shelf covers half of the depth)	180 x 123 cm	Δ ⁽¹⁾	+ 8.0
	200 x 140 cm	Δ ⁽²⁾	+ 12.0
dropside body 150 x 123 cm COMBI		Δ ⁽²⁾	
	COMBI storage box 45 x 125 cm H110 cm	Δ ⁽²⁾	
COMBI waste collection body (1.7 m ³ version)		Δ ⁽²⁾	
watering unit with 600 L tank		Δ	+ 140.0
COMBI high pressure cleaner with 210 L tank and 20 m hose		Δ	
high pressure cleaner with 600L tank and 20 m hose		Δ	+ 150.0
load lashing eyes on loading bed		Δ	
tail lift and dropside body 200 x 140 cm H30 cm with mesh sides extension H55 cm		—	+ 370.0
		—	+ 390.0
tail lift and box van body 200 x 140 cm		—	+ 390.0
isothermal body H120 cm	180 x 123 cm	Δ ⁽¹⁾	+ 120.0
isothermal body H130 cm	200 x 140 cm	Δ ⁽²⁾	+ 140.0
refrigerated body 0 +4 °C with side and rear door	180 x 124 cm	Δ ⁽¹⁾	+ 220.0
	200 x 140 cm	Δ ⁽²⁾	+ 250.0
waste collection body 2.2m ³		Δ ⁽¹⁾	+ 200.0
waste collection body with bin lift system 2.2m ³		Δ ⁽¹⁾	+ 280.0
waste collection body 2.8m ³		Δ ⁽²⁾	+ 240.0
waste collection body with bin lift system 2.8m ³		Δ ⁽²⁾	+ 320.0
tarp system for waste collection body		Δ ⁽¹⁾	+ 15.0
broom and dustpan holder kit		Δ	+ 8.0
semi-trailer coupling system fitting DIN Ø40 drawbar eyes		Δ	+ 60.0



	340 ED	weight [kg]
reverse inching device for easy trailers coupling	Δ	+ 4.0
semi-trailer coupling system with fifth wheel fitting 2" kingpins	Δ	+ 100.0

FRONT / REAR ACCESSORIES

front pin tow hitch	.	
rear ball tow hitch	.	
rear trailer hitch with ball & pin coupling (instead of standard ball hitch)	Δ	+ 3.5
automatic tow hitch fitting DIN Ø40	Δ	+ 15.0
front protective bumper	.	
rear 13 pin connector	.	
show plough hydraulic kit	Δ	+ 10.0
snow plough	!	+ 82.0
electric salt spreader	Δ	+ 50.0
anti-roll kit	—	+ 5.0
rear hydraulic kit	Δ	+ 4.0

TYRES

road tyres (front and rear 175/65 R14)	—	
road tyres (front and rear 175/70 R14)	.	
road tyres (front and rear 175/75 R14)	—	
low-profile road tyres (front and rear 225/55 R12)	.	
turf tyres (front and rear 23x8.50-12 6PR)	—	
turf tyres (front 23x8.50-12 6PR, rear 23x10.50-12 8PR)	!	
off-road tyres (front and rear 23x8.50-12 6PR)	—	
off-Road tyres (front 23x8.50-12 6PR and rear 23x10.50-12 8PR)	!	
spare wheel (provided separately)	Δ	(ext.) +18.0

NOTE

Top speed: approximate, obtained on a flat surface in optimum usage conditions and in SPORT mode. **Maximum negotiable slope:** approximate and assessed with vehicle empty in ideal usage conditions on discontinuous ramps. **Maximum autonomy:** approximate and obtained on a flat surface, in optimum usage conditions, with ECO mode and energy saver and adopting a correct driving style, at a speed no higher than 60% of the maximum speed, for non-continuous use (battery discharged in 5 hours). **Estimated battery lifespan:** approximate figure, based on the information in the manufacturer's possession at the time this file was published. **Maximum towing capacity:** calculated in optimum usage conditions, the trailers must have repulsion brakes and comply with the law. Maximum vertical weight on the tow hitch: 120kg. **The technical specifications indicated in this catalogue** (performance, autonomy, dimensions, etc.) depend - or may depend - on temperature, terrain, driving style, accessories, load or use of the vehicle. The data usually refers to use on a flat surface in optimum usage conditions - i.e. a basic vehicle version with no load and with the lightest battery, on an even and paved road surface with an outdoor temperature of 25°C, the battery fully charged, on board electronic devices switched off, and without any other accessory consumption. **The technical specifications, design and performance levels indicated in this technical data sheet are by way of example only and may be subject to modifications without prior notice.**



Via Cile, 5
35127 Padua | Italy



+39 049 761208



info@alke.com

WWW

www.alke.com



© 2019 Alkè

Rev. 190903



ISO 9001:2015- BN17607/17301
ISO 14001:2015- BN17607/17302
OHSAS 18001:2007- BN17607/17303

The technical specifications, design and performance levels indicated in this technical data sheet are by way of example only and may be subject to modifications without prior notice.